



Specification:

- housing made of galvanized or stainless steel
- holder in the housing for the pump adapter
- painting with powder or thermoplastic paint
- manual stationary bicycle pump max. 10 bar
 - thick piston made of stainless steel AISI304 fi 14 mm
 - stainless steel pump handle fi 32 mm
 - anodized aluminum sealant (PA6)
 - antifog pressure gauge with glycerin
- double chamber anodized aluminum IBOMBO AISIPRO HEAD™ pump adapter for all types of bicycle valves (Presta, Schrader and Dunlop) with industrial grade AISI304 stainless steel internals
- mounting kit (4 x M10 anchors, 75 mm)
- anti-theft nuts for the base of the station with a patent key
- anti-theft screws securing the element of the station with service tips
- branding of the front and two walls of the station with foil and laminate
 - 4 x 10,5 x 54 cm



The **IBOMBO PRS-sv1** public bicycle pump is designed for use in public spaces. The advantage of this model is its small size, which allows it to be installed almost anywhere. In this model, it is not possible to hang the bike on the rack. The construction of the housing is made of a galvanized/stainless steel profile - powder coated or plastic coated. The device is fixed to the ground with anchors. The sheet metal elements of the device are connected with anti-theft screws.



IBOMBO sp. z o.o.

Strzyżewice, ul. Modelarska 9a, 64-100 Leszno, POLAND
KRS: 0000923409, NIP: 6972383411, REGON: 520012450

biuro@ibombo.com | www.ibombo.com | +48 730-070-730

